EUCON HC 370

MID RANGE WATER REDUCING ADMIXTURE



DESCRIPTION

Eucon HC 370 is a mid range water reducing admixture for concrete. This versatile admixture consists of a modified carboxylate polymer which produces high quality concrete economically. Eucon HC 370 shows improved finishing characteristics and provides homogeneous concrete.

PRIMARY APPLICATIONS

- · Used for all cement types.
- Concrete made with SCM

- General purpose ready mix concrete.
- Hot weather concreting

FEATURES/BENEFITS

Plastic Concrete

- Improves finishability
- Improves workability
- · Reduces water requirement

Hardened Concrete

- Increases compressive strength
- Reduces permeability
- Improves finished appearance
- · Reduces shrinkage
- Increases durability

TECHNICAL INFORMATION

PROPERTY	VALUE
Physical state	Straw yellow to brown liquid
Base material	Modified polycarboxylate
Specific Gravity	$1.09 \pm 0.02@27^{\circ}C$
Air entrainment	≤ 1.5% over control mix
рН	Minimum 6
Chloride Content	< 0.2%

Compatible with all cement typeslike OPC, OPC +Fly ash, PSC etc.,

PACKAGING / YIELD

EUCON HC 370 is packaged in bulk 220 kg and 20 kg drums.

SHELF LIFE

1 year in original, unopened package.

SPECIFICATIONS/COMPLIANCES

EUCON HC 370 meets or exceeds the requirements of:

- IS 9103/2007
- ASTM C494, Type G
- AASHTO M 194



DIRECTIONS FOR USE

- Normal dosage range is 200ml 600ml / 50 kg of cement.
- However the optimum dosage is determined by site trials.
- EUCON HC 370 should be added to the initial batch water of the concrete mixture.
- Do not dispense onto dry cement.
- Overdosing leads to retardation of setting times of concrete, mix may segregate and bleeding of concrete.

PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain EUCON HC 370 above freezing; however, freezing and subsequent thawing will not harm the material if thoroughly agitated. Never agitate with air or an air lance.
- Add to mix independent of other admixtures.
- In all the cases, refer Safety Data sheet before use.

